

VITOR⁺ VITOR^{+ZX} LUXTM

Warranty and Maintenance Information

Warranty and Maintenance

- KiwiColour products come with comprehensive written warranties backed by Kiwi Steel, with warranty periods specific to a particular building and location.
- Please request a warranty upon project completion as warranties may not automatically apply. This request should be made within one year of material delivery.
- The warranty periods commence from the date of material delivery to the designated site or upon collection from the rollformer.
- Our residential roofing warranties meet the NZ Building code requiring minimum durability of 15 years.
- Consult with your local KiwiColour supplier or installer for advice on product choice and the required maintenance for the best performance of your KiwiColour product.
- There are specific maintenance requirements that need to be followed to uphold the validity of your KiwiColour warranty which are detailed on the following page.

Perforation and Paint

- The KiwiColour product warranty consists of two parts, the 'perforation' warranty and the 'paint' warranty.
- Perforation warranty covers perforation coming as result of corrosion.
- Paint warranty covers the paint surface against flaking, peeling, and excessive fading.

Environment - Things to Consider

- All environmental factors for the location must be reported to Kiwi Steel before a warranty can be issued.
- If recommended and standard installation practice is not followed then the KiwiColour warranty may be void.
- Warranty periods may differ from standard subject to specific environmental conditions.
- Special consideration should be given for any of following areas.
 - Geothermal Area
 - Adjacent industrial environment
 - Agricultural environment (animal farming etc)
 - Heavy wind area causing a severe coastal environment

Residential

- All warranty periods apply only to residential buildings.
- For other applications such as commercial buildings or schools, please contact the Kiwi Steel team for specific warranty periods. The maximum warranty period offered for non-residential buildings is 15 years.

- Please refer to the General Terms and Conditions for further information on the KiwiColour website at www.kiwicolour.co.nz

Warranty and Maintenance Information

Moderate : ISO Category 1 - 3

- Typically starts 500 – 1000 metres from breaking surf such as is found on exposed coasts

		Roofing	Wall Cladding	Gutter / Downpipe	Fascia
VITOR⁺	Perforation	30	20	10	15
	Paint	18	15	10	10
VITOR^{+ZX}	Perforation	30	20	12	15
	Paint	18	15	10	10
LUX	Perforation	30	20	10	15
	Paint	18	15	10	10
Maintenance	Rain Washing	Rain Washing + Manual Washing every year	Manual Washing Every 6 months	Manual Washing Every 6 months	

Severe : ISO Category 4

- Typically starts 100 – 500 metres from breaking surf such as is found on exposed coasts.
- Light salt deposits, or frequent smell of salt in the air

		Roofing	Wall Cladding	Gutter / Downpipe	Fascia
VITOR⁺	Perforation	20	20	10	15
	Paint	15	15	5	5
VITOR^{+ZX}	Perforation	20	20	12	15
	Paint	15	15	10	10
LUX	Perforation	20	20	10	15
	Paint	15	15	10	10
Maintenance	Rain Washing	Rain Washing + Manual Washing every 6 months	Manual Washing Every 3 months	Manual Washing Every 3 months	

Very Severe : ISO Category 5

- Starts 50m from high water on east coast, 100m from high water on west coast
- Almost constant smell of salt spray. Heavy salt deposits

		Roofing	Wall Cladding	Gutter / Downpipe	Fascia
VITOR^{+ZX}	Perforation	15	15	10	15
	Paint	15	15	10	10
Maintenance	Rain Washing	Rain Washing + Manual Washing every 3 months	Manual Washing Every month	Manual Washing Every month	